

Improved safety when passivating

Avesta FinishOne™ Passivator 630

An acid-free passivator!

Flash clouds or smut, seen as brown staining, can occasionally appear on any stainless steel surface after pickling.

Passivating with Avesta FinishOne™ Passivator 630 eliminates these spots with ease, restoring the surface.

Avesta FinishOne™ Passivator 630, is geared to a wide range of industrial passivating applications. It offers a good general passivating result on stainless steel surfaces. It is suitable for applications such as:

- Passivation after pickling
- Removal of free iron (smut)
- Prevents water staining caused by poor rinse water.

Avesta FinishOne™ Passivator 630

- Restores the passivation layer on stainless steel surfaces that have been damaged during fabrication or usage.
- Further improves the result after pickling and diminishes the risk of discoloured surfaces caused by flash clouds or smut.
- Reduces the formation of toxic nitric fumes during rinsing after pickling
- Creates no hazardous waste, contains no nitric acid.
- Easy to handle, classified as non-dangerous goods.




Avesta FinishOne™ Passivator 630 – efficient and environmentally safe.




Avesta FinishOne™ Passivator 630 – removes free iron (the brown staining seen on the photo.)


Instructions for use




1. Stir the solution before use. Apply the spray with an acid-resistant pump, e.g. Avesta Membrane Pump SP-25 or Hand Pump 415.



2. To avoid smut formation after spray pickling the Passivator shall be applied immediately while the surface is still wet, "wet on wet". Leave the fluid to react 10-15 min.



3. Rinse thoroughly with water, preferably with high pressure water jet.



4. No need to treat the waste water which is neutral and acid-free.

Packaging

Avesta FinishOne™ Passivator 630 is supplied in 25 kg, and 1000 kg polyethylene drums/containers.

Other information

For more information, please visit our website www.avestafinishing.com where you can find Material Safety Data Sheets and other useful information.

Storage

Avesta FinishOne™ Passivator 630 should be stored indoors at room temperature. Containers must be kept properly closed, in an upright position and inaccessible to unauthorised persons.

Worker safety

Protective clothing. Users should wear acid resistant overall, gloves and rubber boots. Goggles or face visor should be used.

Avesta

Finishing Chemicals

Avesta Welding AB Finishing Chemicals
Lodgatan 14, SE-211 24 Malmö, Sweden
Tel: +46 (0)226 821 00, Fax: +46 (0)40 93 94 24
www.avestafinishing.com